



Closure CLS 01

Designed especially for connecting glass fiber cables. The oval entry port means that the closure is suited for uncut cable and that it can be used as a joint and branch-off closure.

- Specifications:
- dimensions Ø 145 mm, height 473 mm
 - plastic casing polypropylene, UV resistant
 - pressure tight up to 0.4 bar
 - temperature range -40 °C to +100 °C
 - capacity
 - max. 6 splice trays (144 splices)
 - max. entries:
 - 1 x oval for uncut cable 2 x Ø 10–25 mm,
 - 4 x round for cable with Ø 10–20 mm,
 - as well as MiniCables and micro tubes

Order number

Closure CLS 01

CLS 01 00 000 000 000 00

The number and type of splice trays (heatshrink or ANT splice), entry kits and mounting kits must be ordered separately.



Closure CLS 03

Designed especially for connecting high fiber cables. The oval entry port means that the closure is suited for working with uncut cable. Fitting of internal strain relief in the shrink area of the closure facilitates the transfer and distribution of the loose tubes considerably. The hinged attachment of the trays enables easy handling of the cables. It permits its use as a joint or branch-off closure.

- Specifications:
- dimensions Ø 216.5 mm, height 483 mm
 - plastic casing polypropylene, UV resistant
 - pressure tight up to 0.4 bar
 - temperature range -40 °C to +100 °C
 - capacity
 - max. 24 splice trays (576 splices)
 - entries:
 - 1 x oval for uncut cable max. 3 x Ø 10–30 mm,
 - 6 x round for cable with Ø 10–30 mm,
 - as well as MiniCables and micro tubes

Order number

Closure CLS 03

CLS 03 00 000 000 000 00

The number and type of splice trays (heatshrink or ANT splice), entry kits and mounting kits must be ordered separately.