



# ALK-3000

## Optical Time Domain Reflectometer



VFL



OLS



OPM



Ethernet Cable test



5-INCH TOUCH LCD COLOR SCREEN



### FEATURES

- ① Full touch-screen Design, realize super fast image processing  
Finger combination control zoom in and out.
- ② Large-capacity Li-battery, can self-charging & reverse charging.
- ③ One-button testing, Event map realize intelligent link analysis.
- ④ Can be expanded to 150G with U disk, large capacity of trace storage.
- ⑤ 5-inch HD capacitive screen, can comply Human-computer interaction unit perfectly.
- ⑥ Multiple wavelengths available.
- ⑦ Realize with light testing self protection system.
- ⑧ Support testing under weak light conditions.

### Packing List



OTDR



Wire Map



AC/AD Charger & Adapter



USB Disk



LED Light



capacitive touch pen



Handle and Belt



Carrying bag



### Parameters

Model	ALK-3000-A	ALK-3000-S
Wavelength (±20nm)	1310/1550	Support online-testing Wavelength 1550nm
Dynamic Range (db)	24/22	22
Pulse width	5ns、10ns、20ns、50ns、100ns、300ns、1.0us、2.5us、10us、20us	
Event Dead zone (m)	2	
Attenuation Dead zone (m)	10	
Distance range (Km)	0.5-160	
Distance uncertainty	± (1 + 0.005 %x Distance + Sampling Resolution)	
Loss Measurement Accuracy	±0.05dB/ dB	
Data sampling point	12800	
Memory Capacity	1000 Curves	
Fiber type	SM	
LCD size	5-inch HD color touch screen	
Capacity of screen touches	>10 Million times	
Standard interface	FC/SC/ST/LC Optional	
VFL		
wavelength	650nm±20	
Output Power	≤2mW Standard	
Standard connector	FC/UPC	
OPM		
Model	A	B
Wavelength Range (nm)	800~1700	800~1700
Detection range(dBm)	-60~+16	-50~+26
Detector type	InGaAs	
Calibration wavelength(nm)	850、980、1300、1310、1490、1550、1625	
Linearity	±5%	
Flange form	FC、SC、LC、ST (Optional)	
OLS		
Wavelength (nm)	1310/1550	
Output Power(dBm)	≥-7	
Ethernet Cable test	Network cable length test	
Network cable test function	can realize network cable open circuit, short circuit, out-of-order test. Roughly detect the fault location of the network cable	
Other		
Battery	4000mAh Li-battery	
Li-battery*	>10 Hours (According to Bellcore TR-NWT-001138)	
Size	165*130*45mm (L×W×H)	
Weight	1Kg	